

CTex LT + CTex LT hot		Mechanical accessories		
				
OPTCTEX Aluminum housing with mounting device to accommodate the Zener barriers (top-hat rail) and the CT electronics		ACCTFB / ACCTFBMH / ACCTFB2 Mounting bracket, adjustable in one axis (M12x1 sensing head, massive housing, mounting of CT sensing head + Laser-Sightingtool)	ACCTTAS Tilt assembly for heads with optical resolution $\geq 10:1$	ACCTKF40B270 / ACCTKF40GE KF40 flange for CT1M, 2M, 3M with B270 window (up to 10^{-7} mbar) / KF40 flange for CTLT with Ge window (up to 10^{-7} mbar)
Advantage: <ul style="list-style-type: none"> Two-piece measuring system with active electronic for evaluation and passive IR receiver (sensing head) CTex sensing head can be installed as passive element in hazardous areas Energy limitation with appropriate zener barriers (STAHL) with approval for zone 1 (PTB 01 ATEX 2053/ E II (1/2) GD [EEx ia/ib] IIC/IIB) 				
		ACCTRAIL Rail mount adapter for CT electronics	ACCTMB Mounting bolt with thread 12x1	ACCTMG Mounting fork, adjustable in 2 axes, with thread M12x1

Optical accessories		
		
ACCTCF / ACCTPW CF-lens or protective window (for LT) for M12x1 sensing head ACCTCFHT / ACCTPWHT for 1M, 2M, 3M	ACCTCFE / ACCTPWE CF-lens or protective window (for LT) with external thread for air purge or massive housing ACCTCFHTE / ACCTPWHT for 1M, 2M, 3M	D08ACCTLST / ACCTOEMLST Laser-Sightingtool (for CT) / OEM Laser-Sightingtool, 635 nm, rotation symmetrical, for connection to CT electronics, power supply via CT electronic box or battery
		
ACCTRAM Right angle mirror for measurements 90° to the sensor axis for sensing heads with optical resolution $\geq 10:1$	ACCTPA + ACCTST20 20 (20 mm length) / ACCTST40 (40 mm length) / ACCTST88 (88 mm length) Pipe adapter with M12x1 internal thread + Sighting tube with M12x1 external thread	

Air purges and protective housings

			
ACCSAP Air purge collar (for heads with optical resolution $\geq 10:1$)	ACCTAPMH Air purge collar for Massive housing (D06/ CSmicro HS/ CTho/ CT P3/ CT P7)	Massive housing of: <ul style="list-style-type: none"> • compact, brass (D06ACCTMHB) • anodized aluminium (D06ACCTMHA) • stainless steel (D06ACCTMHS) 	<ul style="list-style-type: none"> • stainless steel version with CF optics (D06ACCTMHSCF) • stainless steel version for HT CF optics (D06ACCTMHSCFHT)
			
ACCTAPLCFHT Air purge collar, laminar, with integrated CF lens (for 1M/ 2M/ 3M)	ACCTAPL Air purge collar, laminar	ACCTAP / ACCTAP2 (2:1 optics) Air purge for CT heads (not for heads with 32 mm length)	

Combinations

					
ACCTAPL Air purge collar, laminar	ACCTMG Mounting fork	Device adjustable in two axes	ACCTFB2 Mounting bracket for sensing head + Sighting tool	D08ACCTLST / ACCTOEMLST OEM Laser-Sightingtool	Sensing head with Laser-Sighting tool
					
ACCTFB Mounting bracket for M12x1 sensing head	ACCTMB Mounting bolt	ACCTAB Device adjustable in two axes	D06ACCTAPMH Massive housing, stainless steel	ACCTAPMH Airpurge, stainless steel	Massive housing with air purge